



Bearing No.	Boundary dimensions			Basic load ratings(kN)		Limiting speed		Mass kg
	mm			Dynamic	Static	rpm		
	d	D	B	Cr	Cor	Grease	Oil	
7901C	12	24	6	3.3	1.8	28,000	36,000	0.011
7902C	15	28	7	4.7	2.6	24,000	32,000	0.015
7903C	17	30	7	5	2.8	22,000	30,000	0.017
7904C	20	37	9	6.8	4.2	20,000	28,000	0.035
7905C	25	42	9	7.8	5.4	18,000	26,000	0.042
7906C	30	47	9	8.2	6.2	16,000	24,000	0.048
7907C	35	55	10	12	9.1	14,000	22,000	0.075
7908C	40	62	12	14.5	10.6	12,000	20,000	0.11
7909C	45	68	12	16	12.6	10,000	18,000	0.13
7910C	50	72	12	16.5	15	8,000	16,000	0.14
7911C	55	80	13	19.1	17.8	7,500	15,000	0.183
7912C	60	85	13	19.5	18.5	7,000	14,000	0.198
7913C	65	90	13	20.3	20.5	6,500	13,000	0.212
7914C	70	100	16	28.1	27.5	6,300	12,000	0.342
7915C	75	105	16	28.6	29.2	6,000	10,000	0.36
7916C	80	116	16	29	30.5	5,500	10,000	0.381
7917C	85	120	18	39	40.5	5,000	9,000	0.542
7918C	90	125	18	41.2	46	5,000	8,500	0.56
7919C	95	130	18	42.5	48	4,500	8,500	0.604
7920C	100	140	20	48.5	52	4,300	8,200	0.808
7921C	105	145	20	51	57	4,000	8,000	0.83

<b>7922C</b>	110	150	20	52	58	3,800	7,500	0.88
<b>7924C</b>	120	165	22	72	80.1	3,600	7,200	1.15
<b>7926C</b>	130	180	24	77.5	90.1	3,400	7,000	1.54
<b>7928C</b>	140	190	24	79.5	95.5	3,200	6,800	1.64
<b>7930C</b>	150	210	28	102	122	3,000	6,500	2.97
<b>7932C</b>	160	220	28	145.6	167.4	2,800	6,300	3.12