

Designation				Principal dimensions (mm)						Basic load ratings(N)		Basic load ratings(kgf)		Speed ratings(rpm)			Abutment and fillet dimensions (mm)						Weight(g)	
轴承代号				外形尺寸						额定载荷(N)		额定载荷(kgf)		极限转速(rpm)			安装尺寸(mm)						重量(g)	
Open type	With shield	With seal VV	With seal DD	d	D	B	B1	r ⁽¹⁾	r ⁽¹⁾	Cr	Cor	Cr	Cor	Grease 脂润滑		Oil 油润滑	d _a	d _b	Da	Db	r _a	r _b	Open type	With shield
								Min (最小)	Min (最小)					ZZ	D-D	Z								
633	633ZZ	-	-	3	13	5	5	0.2	0.2	1300	485	133	49	40000	-	48000	4.6	6	11.4	11.3	0.2	0.2	3.38	3.33
634	634ZZ1	-	-	4	16	5	5	0.3	0.3	1730	670	177	68	36000	-	43000	6	7.5	14	13.8	0.3	0.3	5.24	5.21
635	635ZZ1	635VV	635DD	5	19	6	6	0.3	0.3	2340	885	238	90	32000	30000	40000	7	8.5	17	16.5	0.3	0.3	8.56	8.34
636	636ZZ	636VV	636DD	6	22	7	7	0.3	0.3	3300	1370	335	140	30000	28000	36000	8	10.5	20	19	0.3	0.3	14	14
637	637ZZ1	637VV	637DD	7	26	9	9	0.3	0.3	4550	1970	465	201	28000	22000	34000	9	12.8	24	22.8	0.3	0.3	24	25
638	638ZZ1	638VV	638DD	8	28	9	9	0.3	0.3	4550	1970	465	201	28000	22000	34000	10	12.8	26	22.8	0.3	0.3	28.3	28.6
639	639ZZ	639VV	-	9	30	10	10	0.6	0.6	5100	2390	520	244	24000	-	30000	13	16.1	26	25.6	0.6	0.6	36.5	36